




# CYRE BEARING LTD

## NTN NKX30T2Z JAPAN Bearing 30 × 42 × 30

Bearing No. NKX30T2Z



NKX30T2Z Bearing 2D drawings and 3D CAD models

Bore Diameter	30 mm
Outer Diameter	48 mm
d	30 mm
Fw	30 mm
D	42 mm
D1	47 mm
D2	48 mm
C	30 mm
a	42,7 mm
r min.	0,6 mm
C1	11 mm
da min.	40 mm
ra max.	0,6 mm
C2	9,5 mm
Weight	0,148 Kg
Dynamic load rating radial (C)	22,3 kN
Dynamic load rating axial (C)	20,4 kN
Static load rating radial (C0)	39,5 kN
Static load rating axial (C0)	42 kN
(Grease) Lubrication Speed	4300 r/min
dw	30 mm
rs min	0.6 mm
Dw	2.5 mm
Dw1	6.35 mm
Lw	15.8 mm



## CYRE BEARING LTD

Lubrication hole on outer ring	Oui/Yes
Precision class	P0
Mass	0.15 kg
Cr	22.3 kN
Ca	20.4 kN
C0r	39.5 kN
C0a	42 kN
Nlim (grease)	4,300 rpm
Nlim (oil)	6,200 rpm
Min operating temperature, Tmin	-20 ° C
Max operating temperature, Tmax	120 ° C
da min	40 mm
ras max	0.6 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.146
Product Group	B04144